



Zebra® ZT400™ Series



SEE MORE. DO MORE.



Keep your critical operations running efficiently with Zebra's durable ZT400 Series printers, designed for years of performance in a wide array of applications.

The ZT400 Series builds on the field-proven reliability of the Z Series™ with advancements in print speed, print quality and connectivity options. Designed for ease of use, the ZT400 Series printers offer an intuitive icon-based LCD graphical user interface and easy-loaded supplies. And, they also include standard USB, Serial, Ethernet and Bluetooth® capabilities. Expanded RFID capacities deliver greater tracking abilities, deeper visibility and enterprise insights.

The ZT400 Series is offered in both 104mm (4") and 168mm (6") models and comes standard with an extensive set of advanced features that ensure your printer investment will always meet your needs, now and in the future. Constructed using an all-metal frame and bi-fold door, this printer is designed to fit well in space-constrained environments.

Featuring Zebra's Link-OS® environment – an innovative operating system combining a powerful Multiplatform Software Development Kit (SDK) and software applications – ZT400 Series printers are easy to integrate, manage and maintain from any location around the globe.

Ideal for These Applications

Manufacturing: work-in-process, product ID/serial numbers, packaging labels, receiving/put-away labelling

Transportation & Logistics: order picking/packing, shipping/receiving, cross-docking, compliance labelling

Retail: distribution centers, back-of-store operations

Healthcare: laboratory labels, blood-bank labels, asset tracking, pharmacy labelling

Link-OS®

ADVANCED INDUSTRIAL PRINTING. RUGGED DURABILITY. LOADED WITH FEATURES.

Designed to grow with your evolving business needs, the ZT400 features increased processing capabilities and an open operating architecture providing flexibility to support your ever-growing and changing application requirements.

Application Flexibility

- Expand your printing readiness through an exceptional range of media capabilities and media delivery options.
- Customise your printer to match your current and future business needs with end-user-installable media handling options.
- Standard Serial, USB, Ethernet and Bluetooth features – as well as two open media slots – allow you to utilise optional connectivity options.
- Expanded RFID capabilities are easy to install and simple to use.
- Ensure quality output for small-label applications with high-resolution printing capabilities.

Effortless to Integrate

- USB host port enables simple printer configuration by easily transferring data from a USB flash drive via mirroring and expanded mapped-drive memory capabilities.
- Virtual Devices apps enable Link-OS printers to support well-known legacy and competitor printer languages – in addition to ZPL[®] and EPL[™] – for a future-proofed investment.

Easy to Operate

- Dynamic QR codes provide on-demand, web-based support to resolve printer errors quickly.
- Print Touch-enabled Link-OS printers offer web page launching features using Near Field Communication (NFC), making it easy to access Zebra's extensive knowledge base of how-to videos and product support.
- Lighted media and ribbon paths make it easy to see inside the printer, even in poorly lit environments.



Simple to Manage

- Zebra's Link-OS environment delivers enhanced capabilities to monitor, manage and maintain your printer from any location.
- Cloud Connect allows Link-OS printers to securely and directly interact with the Cloud for printing and device management.
- Profile Manager enables you to edit and manage one printer, batches of printers or all Link-OS printers across your network anywhere in the world.



COMPARING THE ZT410™ AND ZT420™

The ZT400 Series offers two models: the ZT410 and the ZT420. Compare the features to see which printer best suits your needs.

	ZT410	ZT420
		
Maximum print width	104mm	168mm
Maximum ribbon length	450 m	450 m
Maximum print speed	356mm/s	305mm/s
User Interface	LCD	LCD
Print resolution	203, 300, 600 dpi	203 and 300 dpi
Printer control language	ZPL, EPL, others	ZPL, EPL, others

ZebraCare™ Services

Increase printer uptime and reduce lost productivity and unbudgeted repair costs by selecting a ZebraCare service agreement. A cost-effective means of planning and budgeting for your annual maintenance expenditures, your agreement ensures that trained Zebra technicians will bring your printer back to factory specifications. Zebra offers a variety of plans to fit your budget and business needs.

Genuine Zebra™ Supplies

Zebra provides high-quality supplies solutions for virtually any application:

- The largest selection of pre-tested, labels, tags and ribbons for your ZT400 printer.
- Ability to create custom labels in any size with pre-printed text, graphics and logos.
- Supplies extensively tested to ensure print quality, chemical resistance and adhesive strength.
- ISO 9001:2008 certified



SPECIFICATIONS AT A GLANCE*

Printer Name

ZT410
ZT420

Standard Features

- Print Methods: Thermal transfer and direct thermal printing
- Construction: Metal frame and bi-fold metal media cover with enlarged clear viewing window
- Side-loading supplies path for simplified media and ribbon loading
- Element Energy Equalizer™ (E³) for superior print quality
- Communications: USB 2.0, high-speed, RS-232 Serial, 10/100 Ethernet, Bluetooth 2.1, USB Host
- Back-lit, multiline graphic LCD display with intuitive menu and easy-to-use keypad for quick operation
- Bi-coloured status LEDs for quick printer status
- ENERGY STAR® qualified

Printer Specifications

Resolution

- 203 dpi/8 dots per mm
- 300 dpi/12 dots per mm (optional)
- 600 dpi/24 dots per mm (optional for ZT410 only)

Memory

- 256 MB RAM memory (4 MB user available)
- 512 MB Flash memory (64 MB user available)

Maximum Print Width

104mm/4.09" (ZT410)
168mm/6.6" (ZT420)

Maximum Print Speed

356mm per second/14 ips (ZT410)
305mm per second/12 ips/ (ZT420)

Media Sensors

Dual media sensors: transmissive and reflective

Media Characteristics

Media width (label and liner):

- ZT410
 - 25.4mm/1.00" to 114mm/4.5" tear/cutter
 - 25.4mm/1.00" to 108mm/4.25" peel/rewind
- ZT420
 - 51mm/2.00" to 178mm/7.0" tear/cutter
 - 51mm/2.00" to 171mm/6.75" peel/rewind

Maximum non-continuous label length:
991mm/39"

Print Length

- 203 dpi: 3988mm/157"
- 300 dpi: 1854mm/73"
- 600 dpi: 991mm/39"

Maximum Media Roll Size

203mm/8.0" O.D. on a 76mm/3" I.D. core

Media Thickness

0.058mm/0.0023" to 0.25mm/0.010"

Media Types

Continuous, die-cut, notch, black-mark

Ribbon Characteristics

(Thermal-transfer option only)

Outside Diameter

81.3mm/3.2" O.D. on a 25.4mm/1.0" core

Standard Length

450 m/1476'

Width

51mm/2.00" to 110mm/4.33"

Ribbon Setup

Ribbon wound ink-side out; ribbon wound ink-side in can be used with the optional ribbon spindle

Operating Characteristics

Environmental

- Operating Environment:
 - Thermal transfer: 5° to 40°C /40° to 104°F
 - Thermal direct: 0° to 40°C /32° to 104°F
 - 20% to 85% non-condensing R.H.
- Storage/Transportation Environment:
 - -40° to 60°C/-40° to 140°F/
 - 5% to 85% non-condensing R.H.

Electrical

- Auto-detectable (PFC Compliant) 100-240VAC, 50-60Hz, rated at 100 Watts
- ENERGY STAR qualified

Agency Approvals

- IEC 60950, EN 55022 Class B, EN55024, EN 61000-3-2, EN 61000-3-3
- cTUVus, CE Marking, FCC-B, ICES-003, VCCI, C-Tick, NOM, S-Mark (Arg), CCC, CU, BSMI, KCC, SABS, IN-Metro

Physical Characteristics

	ZT410 closed	ZT420 closed
Width:	269mm/10.6"	336.55mm/13.25"
Height:	324mm/12.75"	324mm/12.75"
Depth:	495mm/19.50"	495mm/19.50"
Weight:	16.33 kg/36 lb.	18.14 kg/40 lb.

Options and Accessories

Communication

- Parallel (Bi-directional interface)
- Wireless: ZebraNet® Printer Server – supports 802.11 a/b/g/n networks via an internally integrated option that enables the use of Webview and Alert features

Media Handling

- Rewind: internally rewinds a full roll of printed labels on 76mm (3") core, or peels and rewinds liner (Factory installed only)
- Peel: Front mount, passive peel option
- Peel: Liner take-up option – additional full roll liner take-up spindle accommodates standard printer base
- Cutter: Front mount guillotine cutter and catch tray
- 25.4mm (1") I.D. Core media supply hanger
- Ink-side in ribbon supply spindle

RFID

- Supports tags compatible with UHF EPC Gen 2 V1.2/ISO 18000-6C
- Integrated RFID system is user-upgradable in the field and available on both 104mm and 168mm models
- Adaptive Encoding Technology automatically selects optimum encode settings

Keyboard Display Unit

Supports KDU Plus™ and ZKDU: Enter variable data and retrieve stored forms for standalone applications

Link-OS Solutions

Software Tools

- Document Design: Quickly design a customized print solution using your business data and Zebra's intuitive, plug-and-print design tools.
- Device Integration: Zebra offers apps and products designed to help you integrate Zebra devices into your existing systems.
- Device Management: Manage your print operations locally and globally with Zebra's suite of device management tools.
- Developer Tools: Provides you the tools you need to create your own apps, including documentation, source code, programming languages, templates and more.

Firmware

- Resident ZPL, ZPL II® and EPL programming languages, selectable through software or front panel.
- XML-enabled Printing — allows XML communications for barcode label printing.

Barcode Symbolologies

- Linear Barcodes: Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case Codes, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2- or 5-digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar, Planet Code
- 2-Dimensional Barcodes: Codablock, PDF417, Code 49, DataMatrix, MaxiCode, QR Code, TLC 39, MicroPDF, RSS-14 (and composite), Aztec

Fonts and Graphics

- 16 resident expandable ZPL II bitmap and two resident scalable ZPL fonts
- Asian and other international scalable and smooth bitmapped fonts
- Unicode: For multi-language printing
- Downloadable objects include graphics, scalable and bitmap fonts, label templates and formats
- IBM Code Page 850 international character sets are available in the fonts A, B, C, D, E, F, G and O through software control
- Code Page 1250, 1252, 1253, 1254, 1255 Support with font O



Zebra Technologies – EMEA Headquarters & Sales Office

Zebra Technologies Europe Limited, Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5XF, United Kingdom
Telephone: +44 (0)1628 556000 Fax: +44 (0)1628 556001 Email: mseurope@zebra.com Web: www.zebra.com

Other EMEA Locations

Europe: France, Germany, Italy, the Netherlands, Poland, Russia, Spain, Sweden, Turkey
Middle East & Africa: Dubai, South Africa